


BLK,TPU,4X28,S-B,AWM General Purpose Cable – Reelfast™ Bulk Cable



Features



- UL/CSA AWM 300V
- General Purpose Cable
- Black TPU jacket, shielded, 4X28 AWG
- -40 Cold Bend Rating
- Flame Ratings: UL1061, CSA FT1

Technical data

Type	BLK,TPU,4X28,S-B,AWM
ID no.	RF50862
Cable data	
Cable Platform	General Purpose Cable
Total number of conductors	4
Cable diameter	Ø 5.21 mm
Cable jacket	TPU, Black
Braid material	38 AWG, TC (Tinned Copper), 90% coverage
Conductor diameter	0.035 "
Conductor material	TC (tinned copper)
Conductor insulation material	PP
Conductor size	4 x 28 AWG [Similar to 0.08 mm ²]
Number of strands x O.D.	19 x 40 AWG
Conductor colors	GN, BK, WH, RD
Weight	0.076 lbs. /meter
Electrical properties at +20 °C	
Voltage	UL/CSA AWM 300V
Dielectric withstand (min.)	2 KVAC
DC resistance (max)	64.9 Ω/1000ft max.
Mechanical and chemical properties	
Bending radius (static)	≥ 5 x Ø
Bending radius (dynamic)	≥ 15 x Ø
Cold bend rating	-40 °C

Technical data

Ambient temperature range (static)	-40 °C...+80 °C
Ambient temperature range (dynamic)	-40 °C...+80 °C
Temperature range (installation)	-20 °C...+80 °C
Approval	
UL Approvals	UL 758 AWM 20233
CSA Approvals	CSA AWM I/II A/B CSA FT1
Compliances	RoHS
Note	
	- Flex ratings may be reduced if used in extreme temperatures, exposure to certain chemicals, operating above the rated cycle speed, or operating below the rated cable bend radius.
	- We reserve the right to make technical alterations without prior notice.