


GRY,PVC,4X22,AWM,VF General Purpose Cable – Reelfast™ Bulk Cable



Features



- UL/CSA AWM 300V
- General Purpose Cable
- Gray PVC jacket, 4X22 AWG
- -40 Cold Bend Rating
- Flame Ratings: UL1061, CSA FT1

Technical data

Type	GRY,PVC,4X22,AWM,VF
ID no.	RF50921
Cable data	
Cable Platform	General Purpose Cable
Total number of conductors	4
Cable diameter	Ø 4.45 mm
Cable jacket	PVC, Gray
Conductor diameter	0.046 "
Conductor material	BC (bare copper)
Conductor insulation material	PP
Conductor size	4 x 22 AWG [Similar to 0.34 mm ²]
Number of strands x O.D.	7 x 0.0096 "
Conductor colors	BN, WH, BU, BK
Weight	0.065 lbs. /meter
Electrical properties at +20 °C	
Voltage	UL/CSA AWM 300V
Dielectric withstand (min.)	2 KVAC
DC resistance (max)	17.5 Ω/1000ft max.
Mechanical and chemical properties	
Bending radius (static)	≥ 5 x Ø
Bending radius (dynamic)	≥ 10 x Ø
Cold bend rating	-40 °C
Ambient temperature range (static)	-40 °C...+80 °C

GRY,PVC,4X22,AWM,VF| 11/11/2021 16-15 | technical changes reserved

Technical data

Ambient temperature range (dynamic)	-40 °C...+80 °C
Temperature range (installation)	-20 °C...+80 °C
Approval	
UL Approvals	UL 758 AWM 2464
CSA Approvals	CSA AWM I/II A/B CSA FT1
Compliances	RoHS CE
Note	
	- Flex ratings may be reduced if used in extreme temperatures, exposure to certain chemicals, operating above the rated cycle speed, or operating below the rated cable bend radius.
	- We reserve the right to make technical alterations without prior notice.