


BLK,FEP,3X18,CMP

General Purpose Cable – Reelfast™ Bulk Cable



Features



- CM 300V
- General Purpose Cable
- FEP, Black, 3X18 AWG
- -40 Cold Bend Rating
- Flame Ratings: NFPA 262

Technical data

Type	BLK,FEP,3X18,CMP
ID no.	RF52172
Cable data	
Cable Platform	General Purpose Cable
Total number of conductors	3
Cable diameter	Ø 5.13 mm
Cable jacket	FEP, Black
Conductor diameter	0.07 "
Conductor material	TC (tinned copper)
Conductor insulation material	FEP
Conductor size	3 x 18 AWG [Similar to 0.75 mm ²]
Number of strands x O.D.	19 x 0.0092 "
Conductor colors	RD, GN, BK
Weight	0.119 lbs. /meter
Electrical properties at +20 °C	
Voltage	CM 300V
Dielectric withstand (min.)	2 KVAC
DC resistance (max)	7.22 Ω/1000ft max.
Mechanical and chemical properties	
Bending radius (static)	≥ 5 x Ø
Bending radius (dynamic)	≥ 10 x Ø
Cold bend rating	-40 °C
Ambient temperature range (static)	-40 °C...+150 °C

Technical data

Ambient temperature range (dynamic)	-40 °C...+150 °C
Temperature range (installation)	-20 °C...+150 °C
Approval	
UL Approvals	UL 444 CMP
CSA Approvals	UL 444 CMP
Compliances	RoHS
Note	
	- Flex ratings may be reduced if used in extreme temperatures, exposure to certain chemicals, operating above the rated cycle speed, or operating below the rated cable bend radius.
	- We reserve the right to make technical alterations without prior notice.