

FS SPACER CLAMP, 1.57"–2.48"



FEATURES

Provides support for nVent ERIFLEX Flexibar and insulated braided conductors without damaging the insulation

Ensures correct spacing for optimum cooling

Supports up to four conductors in parallel

Easy to install

Spacers are halogen free

RoHS compliant

PRODUCT ATTRIBUTES

Finish: Electrogalvanized

Material: Steel;Polyamide

Working Temperature: -40 to 266 °F

Flammability Rating: UL® 94HB

Conductor Width: 1.57" – 2.48"

Length: 6.540"

Height: 3.740"

Hole Size: 0.330"

A: 5.900"

Unit Weight: 0.220 lb

ADDITIONAL PRODUCT DETAILS

Recommended distance between supports is 400 mm (15 3/4").

CERTIFICATIONS



North America

+1.800.753.9221

Option 1 – Customer Care

Option 2 – Technical Support

Europe

Netherlands:

+31 800-0200135

France:

+33 800 901 793

Europe

Germany:

800 1890272

Other Countries:

+31 13 5835404

APAC

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Our powerful portfolio of brands:

nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER

© 2022 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

nVent reserves the right to change specifications without notice.